

### Technical data



## MULTISPLIT AROMA2



Auto restart

LED Display

Defrost function

Auto diagnosis

Auto clean

Remote control

Dehumidifier

3D Air

Drain on both sides

### MODEL

| MODEL                        |                        |        | GIA-MSI-07AR2R32          | GIA-MSI-09AR2R32 | GIA-MSI-12AR2R32 | GIA-S18AR2B-R32-I | GIA-S24AR2B-R32-I |
|------------------------------|------------------------|--------|---------------------------|------------------|------------------|-------------------|-------------------|
| Power supply                 |                        | V,P,HZ | 220-240V (1 Phase ~ 50Hz) |                  |                  |                   |                   |
| <b>PERFORMANCE</b>           |                        |        |                           |                  |                  |                   |                   |
| Cooling                      | Power                  | kW     | 2,05                      | 2,6              | 3,5              | 5,3               | 7,0               |
|                              |                        | Btu/h  | 7.000                     | 9.000            | 12.000           | 18.000            | 24.000            |
| Heating                      | Power                  | kW     | 2,34                      | 2,9              | 3,8              | 5,6               | 7,3               |
|                              |                        | Btu/h  | 8.000                     | 10.000           | 13.000           | 19.000            | 25.000            |
| <b>FEATURES</b>              |                        |        |                           |                  |                  |                   |                   |
| Indoor unit                  | Sound power            | dB(A)  | 54                        | 53               | 53               | 55                | 59                |
|                              | Sound pressure (H/M/L) | dB(A)  | 40/30/26/21               | 40/34/26/21      | 40/34/26/22      | 44/37/30/25       | 44,5/42/34,5/28   |
|                              | Air flow               | m³/h   | 520/460/340               | 520/460/360      | 600/500/360      | 840/680/540       | 980/817/662       |
|                              | Operation temperature  | °C     | 17~30/0~30                | 17~32/0~30       | 17~32/0~30       | 17~32/0~30        | 17~32/0~30        |
| <b>DIMENSIONS AND WEIGHT</b> |                        |        |                           |                  |                  |                   |                   |
| Indoor unit                  | Net dimensions (LxHxD) | mm     | 805x285x194               | 805x285x194      | 805x285x194      | 957x302x213       | 1.040x327x220     |
|                              | Net weight             | kg     | 7,5                       | 7,5              | 7,5              | 10                | 12,3              |
| <b>CONNECTIONS</b>           |                        |        |                           |                  |                  |                   |                   |
| Cooling pipe                 | Liquid - Gas           | inch   | 1/4"-3/8"                 | 1/4"-3/8"        | 1/4"-3/8"        | 1/4"-1/2"         | 3/8"-5/8"         |
|                              | Connection             | mm     | 3x2,5+T                   | 3x2,5+T          | 3x2,5+T          | 3x2,5+T           | 3x2,5+T           |